

Silencer Specification

MAXIM

• SILENCERS •

OVERVIEW

Constructed of 316L stainless steel, the MP41 offers very high noise attenuation in marine exhaust systems where water is injected upstream of the silencer. Mixed exhaust flow temperature not to exceed 200° F at silencer inlet.



Typical Applications: Internal combustion engines using wet type exhaust

FEATURES

- Advanced acoustical design
- Reduces noxious fumes and odors
- Thick wall construction for high transmission loss
- All welded construction and long service life
- Standard pipe size O.D. stubs
- Easy installation in any position

OPTIONS / ACCESSORIES

- Monel construction
- Flanged connections
- Horizontal or vertical support arrangements
- Complete range of exhaust accessories



PRODUCT SPECS

| Model-Size | A (size) | B (dia) | C | D (OAL) | Est Wt |
|------------|----------|---------|----|---------|--------|
| MP41-4 | 4 | 10.75 | 48 | 54 | 83 |
| MP41-4.5 | 4.5 | 12.75 | 48 | 54 | 103 |
| MP41-5 | 5 | 12.75 | 48 | 54 | 103 |
| MP41-6 | 6 | 14.75 | 48 | 54 | 118 |
| MP41-8 | 8 | 18.75 | 48 | 60 | 167 |
| MP41-10 | 10 | 22.25 | 58 | 70 | 235 |
| MP41-12 | 12 | 26.25 | 70 | 6 | 334 |

- All dimensions are in inches. All weights are in pounds. Weights are approximate.
- Listed sound data is based on typical performance and should not be considered absolute.
- See nomenclature guide for additional information on part number creation.